


## **CLASS 1, DIVISION 1 / ZONE 0,1 INSTALLATION DRAWING** FOR TWO WIRE PROXIMITY PROBES

USE CSA, ATEX, AND/OR IECEX APPROVED BARRIERS FOR GROUP IIC

## **HAZARDOUS AREA**



- **GROUNDED**
- ► EXTENSION CABLE USED TO BE APPROVED BY LOCAL **JURISDICTION**
- ▶ TWO WIRE INSTALLATION SHOWN. FOR USE WITH OR WITHOUT 4-20 mA MODELS
- ► SEE SAFETY BARRIER MANUFACTURER INSTALLATION MANUAL FOR INFORMATION ON PROPER WIRING OF CABLES TO THE TERMINAL BLOCKS OF THE SAFETY BARRIER
- ONE DUAL OR SINGLE CHANNEL IIC BARRIER CAN BE USED WITH THIS CONFIGURATION
- ▶ WIRE COLOR FOR CLARITY ONLY
- ▶ BNC NOT FOR USE IN HAZARDOUS AREA
- ▶ TYPE 4 IS AN OUTDOOR RATING, IF UNIT IS MOUNTED INDOORS, AN INDOOR RATED TYPE 4 ENCLOSURE APPROPRIATE FOR THE APPLICATION CAN BE USED.